

Felefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de e-mail: info@ampri.de

# **Technical Data Sheet**


**4M**Pri

Article-No.: 01172

Description: STYLE Graphite

Nitrile examination glove

graphite, non sterile, powder free





PRODUCT DESCRIP	TION						
material	Latex	✓ Nitrile	□ Vinyl	☐ Vinyl-Nitrile- mixture	Polyethy-lene (PE)	☐ TPE	□ cotton
colour	white	☐ blue	black	☐ mint	☐ purple	☐ mix	☑ graphite
characteristics	☐ prepowdered	powderfree	sterile	non sterile	☑ ambidex-	☐ fits hand-	accelerator-
					trous	specific	free
surface	☐ full textured	✓ finger textured	not textured	embossed	chlorinated ins	side	
SIZES							
	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)	XXL (10-11)	XXXL (11-12)
width	≤ 80 mm	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	-	-
length	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-	-
REGULATORY AFFA	AIRS						
PPE-Regulation	☐ Category I	☐ Category II	Category III	☐ no PPE-article			
(EU) 2016/425							
MD-Regulation	☑ Class I	☐ Class II a	☐ Class III	☐ sterile	☐ measuring	no medical	CE
(EU) 2017/745					function	device	
Food Contact	☑ acidic foods	☑ aqueous	✓ fatty foods	☑ alcoholic	☑ dry foods	☐ not approved	
(EG) 1935/2004		foods		foods		for food-	<b>52</b> "
						contact	, , ,
STANDARDISATION	1			J			J
EN 388 Mechanical	abrasion	blade cut	tear resistance	puncture	blade cut	impact tost	
Risks	resistance	resistance	tear resistance	resistance	resistance	impact test	
LISKS				resistance	resistance		
Level	not applicable	Coupe-Test			TDM-Test		
			code letter	level		degradation	
Level	not applicable	Coupe-Test	code letter		TDM-Test	degradation 15,1 %	ISO 374-1/Type B
Level EN 374-1	not applicable  chemical	Coupe-Test		level	TDM-Test permeation time	-	ISO 374-1/Type B
Level EN 374-1	not applicable  chemical Sodium hydroxide	Coupe-Test 40% e 30%	К	level 6	permeation time > 480 min	15,1 %	ISO 374-1/Type B
Level EN 374-1 Chemical Risks	not applicable  chemical Sodium hydroxide Hydrogen Peroxide	Coupe-Test 40% e 30%	K P		permeation time > 480 min > 30 min	15,1 % -74,1 %	ISO 374-1/Type B
Level EN 374-1 Chemical Risks EN 374-4	not applicable  chemical Sodium hydroxide Hydrogen Peroxide	Coupe-Test 40% e 30%	K P		permeation time > 480 min > 30 min	15,1 % -74,1 %	
Level EN 374-1 Chemical Risks EN 374-4 Degradation	not applicable  chemical  Sodium hydroxide  Hydrogen Peroxide  Formaldehyde 37%	40% e 30%	K P T		permeation time > 480 min > 30 min > 240 min	15,1 % -74,1 % 24,0 %	KPT
Level EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5	not applicable  chemical  Sodium hydroxide  Hydrogen Peroxide  Formaldehyde 37%	40% e 30%	K P T		permeation time > 480 min > 30 min	15,1 % -74,1 % 24,0 %	KPT 8N 150 374-52016
Level EN 374-1 Chemical Risks EN 374-4 Degradation	not applicable  chemical  Sodium hydroxide  Hydrogen Peroxide  Formaldehyde 37%	40% e 30%	K P T		permeation time > 480 min > 30 min > 240 min	15,1 % -74,1 % 24,0 %	KPT
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness	not applicable  chemical  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	40% e 30% 6	K P T T Sms (viral, bacteria	level 6 2 5	permeation time > 480 min > 30 min > 240 min	15,1 % -74,1 % 24,0 %	KPT  BN 150 274 5-2016
Level EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism	not applicable  chemical  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	40% e 30% 6	K P T	level 6 2 5	permeation time > 480 min > 30 min > 240 min	15,1 % -74,1 % 24,0 %	KPT  BN 150 274 5-2016
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	40% e 30% 6 against microorganis	K P T T Sms (viral, bacteria according to EN ISO 21	level 6 2 5 and fungi). Test acco	permeation time > 480 min > 30 min > 240 min  ording to ISO 16604	15,1 % -74,1 % 24,0 %	KPT  BN 150 274 5-2016
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	40% e 30% 6 against microorganis	K P T T Sms (viral, bacteria according to EN ISO 21	level 6 2 5	permeation time > 480 min > 30 min > 240 min  ording to ISO 16604	15,1 % -74,1 % 24,0 %	KPT  EN 150 274 5-2016  VIRUS
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	40% e 30% 6 against microorganis	K P T T Sms (viral, bacteria according to EN ISO 21	level 6 2 5 and fungi). Test acco	permeation time > 480 min > 30 min > 240 min  ording to ISO 16604	15,1 % -74,1 % 24,0 %	KPT  BN 150 274 5-2016  VIRUS
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th	Coupe-Test  40% e 30% 6  against microorganis ne requirements accome requirements accome	K P T T sms (viral, bacteria a	level   6   2   5   5	TDM-Test	15,1 % -74,1 % 24,0 %	KPT  EN 150 274 5-2016  VIRUS
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th	40% e 30% 6 against microorganis ne requirements accome requirements accome	K P T T sms (viral, bacteria a	level   6   2   5   5	permeation time > 480 min > 30 min > 240 min  ording to ISO 16604	15,1 % -74,1 % 24,0 %	KPT  KPT  KPT  KPT  KISD 296-2096  VIRUS  EN  455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th	40% e 30% 6 against microorganis ne requirements accome requirements accome	K P T T sms (viral, bacteria a	level   6   2   5   5	TDM-Test	15,1 % -74,1 % 24,0 %	KPT  EN 159 375-32916  VIRUS
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1 freedom from holes	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th  The glove has an A general Inspection	40% e 30% 6 against microorganis ne requirements accome requirements accome	K P T T sms (viral, bacteria a	level   6   2   5   5	TDM-Test	15,1 % -74,1 % 24,0 %	KPT  KPT  KPT  KPT  KISD 296-2096  VIRUS  EN  455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1 freedom from holes	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th	40% e 30% 6 against microorganis ne requirements accome requirements accome	K P T T sms (viral, bacteria a	level   6   2   5   5	TDM-Test	15,1 % -74,1 % 24,0 %	KPT  KPT  KPT  KPT  KISD 296-2096  VIRUS  EN  455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1 freedom from holes	not applicable  chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th  The glove has an A general Inspection	40% e 30% 6 against microorganis ne requirements accome requirements accome	K P T T sms (viral, bacteria a	level   6   2   5   5	TDM-Test	15,1 % -74,1 % 24,0 %	KPT  KPT  KPT  KPT  KISD 296-2096  VIRUS  EN  455



21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de

e-mail: info@ampri.de

# **Technical Data Sheet**

Article-No.: 01172

Description: **STYLE Graphite** 

Nitrile examination glove

graphite, non sterile, powder free

LOGISTIC DATA		
generell information material	n	carton
pieces per subpacki	100	
GTIN subpacking siz	4044941734316	
GTIN subpacking siz	4044941734430	
GTIN subpacking siz	4044941734430	
GTIN subpacking siz	4044941734334	
GTIN subpacking siz	4044941734378	
GTIN subpacking siz	4044941734392	
GTIN subpacking siz	-	
PZN subpacking size	19149029	
PZN subpacking size	19149029	
PZN subpacking size	19149058	
PZN subpacking size	19149064	
PZN subpacking size	19149070	
PZN subpacking size	-	
PZN subpacking size		
measures & size	. 7001	
length	215 mm	
width		120 mm
heigth	60 mm	
weights		
size	net weight	gross weight
XS	300 g	360 g
S	360 g	420 g
М	380 g	440 g
L	410 g	470 g
XL	450 g	510 g
XXL	-	-
XXXL	-	-

LOGISTIC DATA	PALETTE		
general information	n		
kind of palett		euro-palette	
measures & size			
cartons per layer		10	
layers per palette		8	
heigth of the palette		199 cm	
weights			
size	net weight	gross weight	
XS	328 g	353 g	
S	376 g	401 g	
M	392 g	417 g	
L	416 g	441 g	
XL	448 g	473 g	
XXL	-	-	
XXXI	-	-	



LOGISTIC DATA	OUTER PACKING	
generell informatio		
material	carton	
subpackings per ou	10	
GTIN outer packing	4044941734323	
GTIN outer packing	4044941734347	
GTIN outer packing	4044941734361	
GTIN outer packing	4044941734385	
GTIN outer packing	4044941734408	
GTIN outer packing	-	
GTIN outer packing	-	
PZN outer packing s	ize XS	=
PZN outer packing s	ize S	-
PZN outer packing s	-	
PZN outer packing s	-	
PZN outer packing s	-	
PZN outer packing s	-	
PZN outer packing s	-	
measures & size		
length		315 mm
width	255 mm	
heigth	230 mm	
weights		
size	net weight	gross weight
XS	3.600 g	4.100 g
S	4.200 g	4.700 g
М	4.400 g	4.900 g
L	4.700 g	5.200 g
XL	5.100 g	5.600 g
XXL	-	-
XXXL -		-





## AMPri Handelsgesellschaft mbH

Benzstraße 16

21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

## **Technical Data Sheet**

Article-No.: 01172

Description: STYLE Graphite

Nitrile examination glove

graphite, non sterile, powder free



## WARNINGS AND SAFETY INFORMATION

storage /	expiry
storage /	

Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

#### use and control

Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical.

Before use, the gloves must be checked for holes or damage.

## disposal

Used gloves must be disposed of after contact with chemicals in accordance with the disposal regulations for the chemical and the regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

## disinfection

Disinfection is not intended for these gloves and is the responsibility of the user.

### warnings/ allergy information

Protective gloves are intended for single use only.

This product contains dithiocarbamates, which may cause allergic reactions

# donning and doffing instructions











rev-no.: 2

date 10.09.2024

changes and errors excepted